## Engineer's Dream Strongest Design in Any Florida Home

Deepest water in Brevard. Home designed to withstand 200mph winds for a buyer who appreciates the design and engineering that make this the safest house in Florida.

Site High and dry river-to-river with 14' depth in waterway, 11' at east dock on Banana River, 7' at west dock on Indian River.

Seawall not needed due to high solid coral rock ridge

**Dock** Mooring for 3 boats up to 50'

10,000 pound covered boat lift

Dock 7' wide with 2 x 12 stringers and fish cleaning table

110v electric panel, water and light

Pool 24,000 gallon, saline chlorination system, popup cleaning heads, 8 person spa

Generator Automatic transfer switch ties into main house panel. 500 gal buried propane tank

UPPER FLOOR 34' x 28' Greatroom. 18' ceilings, entertainment center, & fireplace wall.
Master bedroom walk-in closet, large shower, and jetted hot tub.
Guest bedrooms and full bath have separate electric and A/C.
Handicap Friendly - all doorways 3' wide
All windows are Dade County hurricane approved impact glass, vinyl clad, double glazed.

**GROUND LEVEL** 4-car garage, workshop, 2 offices, utility room, pool bath and play area.

Step by step construction photo album available by request

## Structural Details

**Footers** reinforcing steel drilled and epoxied into bedrock, 3' x 1' continuous 5' x 5' x 2' column pads 1<sup>st</sup> Floor 12" CMU poured with #5 reinforcing rods 16" on center hooked & tied at footing & tie beams Concrete Columns: Minimum 24" x 12" with six #6 reinforcing rod Tie Beams: Minimum 24" x 12" with six #6 reinforcing rod 2<sup>nd</sup> Floor Framed with 18 gauge 6" steel studs 12" Core Slab (structural beam) system with 2" slab over-pour East & west window walls fabricated with 8 x 8 x <sup>1</sup>/<sub>2</sub> structural steel Structural Columns: 8 x 8 x <sup>1</sup>/<sub>2</sub> structural tubing Anchor Bolts: 1<sup>1</sup>/<sub>4</sub> "diameter, all connection bolts, <sup>3</sup>/<sub>4</sub>" high-strength. Roof Rafters: 14" beams - 54# per foot **Roof** 20-gauge galvanized aluminum standing seam **Electrical** 400 amp, all copper wiring **HVAC** one 5 ton unit, one 3 ton unit Fireplace refractory flue, firebrick liner, coral face **Ceiling** R-33 insulation, tongue & groove cypress throughout Exterior stairs & canopy structural aluminum with commercial powder-coat finish. Elevator 1000 pound Hydraulic **Driveway** 6" thick 4,000 PSI structure fiber

Appraisal must be done by qualified appraiser/engineer

Marketed by: Richard Webb 321-480-5514 Virtual Tour: <u>www.4Brevard.com/hotlist.htm</u>

